

Continue



Honeywell pro 2000 thermostat owner's manual

If your TH2210DH/TH2110DH thermostat has a blank display, try replacing batteries if it's battery-powered or powering it up with batteries if it's common wired. If the issue persists, you may need to consult a technician. For error message "Lo Bat", simply replace the battery. To turn on/off heating/cooling, locate the system Slider Switch labeled Heat Off Cool, slide the switch to the desired setting, and manually adjust the arrows or establish a schedule. To program the schedule, press the Set button three times until "Set Schedule" appears. Then, set the start time of each period (Wake-Fri) by pressing the up/down buttons. Next, set the temperature for heating/cooling modes (Heat/Cool). For each subsequent period, repeat steps 2-6. Once done, press the Run button to save changes and exit. To skip a period, press the Hold button for four seconds while that period is displayed. To bypass the schedule from the main screen, simply press the Hold button. Note: The changes are also saved if you don't press any button within 60 seconds. Press up or down to immediately change the temperature for a short period. The display will show "Temporary" and the program period will flash. The new temperature will be used until the next period starts. To make the override permanent, press up or down until the desired temperature is shown, then press the Hold button. Press the Run button to cancel and return to the schedule. Make sure the heat-off-cool switch is set correctly. After setting your preferred temperature, the thermostat will automatically switch back to showing the room temperature, which is normal. You can also set the clock time by pressing the Set button and using the up or down arrows. To select a day of the week, press the Set button again and use the up or down arrows. Press Run to save your changes and exit. This thermostat works with standalone heat pumps as well as those with auxiliary or backup heat. To access the installer setup on this series 2000 thermostat, press and hold both up and down buttons until the display changes (about 5 seconds). To change settings, use one of these methods: - Press the up or down button to adjust a setting - Press the up and down buttons together for one second to move to the next function - Press the Run button to exit and save your changes. How to Fix a Blank Display on Your TH2210DH/TH2110DH Thermostat To resolve a blank display issue with your thermostat, start by checking or replacing the batteries if it's battery-powered. If that doesn't work, try powering it up with batteries. For common wired devices, check breakers, furnace power switches, and kill switches to ensure system power is on. Fixing Heating/Cooling Issue To turn heating/cooling on/off, locate the Heat Off Cool Slider Switch and slide it to your desired setting. Manually adjust arrows or establish a schedule using arrows and press hold. For series 2000 thermostats, press and hold up and down buttons for 5 seconds to enter System Setup. Accessing Installer Setup Press and hold both up and down buttons until the display changes (approximately 5 seconds) to access installer setup. Changing settings: Press up/down button to change setting, up/down simultaneously for one second to advance function, and RUN button to exit and save settings. Programming Schedule on TH2210DH/TH2110DH Thermostat To program schedule, slide Heat Off Cool switch to desired setting and manually adjust arrows or press hold. For 2000 family schedules, press Set button three times until "Set Schedule" appears. Adjust start time for weekdays (Mon-Fri) by pressing up/down buttons. Set temperature and switch between heating and cooling modes as needed. Press the up or down button to set the temperature and press Set. The next period's start time will flash, then repeat steps for each remaining period. Once done, press Run to save changes and exit. To skip a period, hold the Hold button for 4 seconds while it's displayed. If you want to bypass the schedule, press Hold from the main screen. Temporarily override the temperature by adjusting it with up or down; "Temporary" will appear on the display. Press Hold to maintain the new temp indefinitely. The word Hold will appear on the screen; pressing Run will cancel the override and resume the schedule. Ensure the heat-off-cool switch is set correctly, as the thermostat will change back to room temperature after setting the desired setpoint and hold. Set the clock time by pressing SET then up or down arrows. Select the day of the week in the same manner, then press RUN to save & exit. For a blank display on your TH2210DH/TH2110DH, check if it's battery powered; replace batteries if necessary. If common wired, try powering it with batteries; if that doesn't work, involve a technician. Check breakers, furnace power switch, and furnace door kill switch to ensure the system is powered up correctly. If your system is fine but works only on batteries, you may need professional help. Replace the battery when seeing an error message "Lo Bat" - it means low battery; replace with new ones to resolve the issue.